

Technical requirements

HAYDAMAKY I STASIUK

Updated 13/06/2019 (5 pages)

Please read carefully prior to signing contract.

Please distribute a copy of this rider to all staff involved in the technical set up.

GENERAL

- To make concert «Haydamaky I Stasiuk» possible it's necessary to follow out ALL the items of this document. Otherwise band reserves the right to:
 - Cancel the concert without return of payment
 - Hang up the doors opening and keep technical check till all technical defects of the system will be recovered, or out-of-service or inapplicable (to items of this document) equipment will be replaced
- The performance space must be technically prepared and available exclusively to Artist for a technical check
- All technical set-ups must be completed before Artist arrives on site. Sufficient personnel shall be present to assist in the technical check and, if needed, make adjustments. These personnel must remain present on the premises until the technical rehearsal has been completed
- If you have any question or problem according to any item of this document - please contact us!!!

SOUND

Sound engineer:

Yurii Naumenko +380 63 207 1962, e-mail: rezozvuk@gmail.com

- We need **2 (two) hours** of pure time for sound check
- The sound engineers and technician will arrive 1 hour before the beginning of Sound Check with the band. All components of sound system must be installed, plugged and checked before their arriving.
- Presence of sound operator plus minimum 1 stage man during whole sound check is obligatory.

SOUND EQUIPMENT:

- **Main Stereo PA:**

1. d&b audiotechnik, Meyer Sound, L-Acoustics, Adamson, EAW
2. Active division on 3-4 lines: Sub, Low, Mid, Hi
3. Power and configuration of the system has to be coordinated with band's sound engineer. But system can't be less 5000 Watt/RMS even in the smallest venue.
Pointer: sound pressure 105 dB in the acoustic center of venue
4. If you don't use fabric (standard) presets, system processor has to be unlocked and available for changing all preferences.
5. In the venue more than 1000 people capacity the usage of line array is obvious. Calculating of power – 1000 Wt./RMS for 100 people!

- **FrontFill:**

1. Acoustic of small sizes and low power for amplification first rows in a big venue, open air and in venues with wide stage
2. Two-four low-profile cabinets, minimum 300 Wt. each.

FOH:

FOH location should be exactly in the center of action of sound components, in front of the stage. To count the right FOH location, please use the rule of isosceles triangle. No any exceptions – FOH can't be behind or sideways of the stage, behind the screen, in acoustic hole. Sound engineer should have possibility to see the whole stage.

FOH Limiters/Compressors

1. It's impossible to use artificial limiters in system. Possible to use only fabric presets of limitation of level
2. Customer and equipment supplier promise to provide full and unobstructed access for sound engineer to all parts of sound system.

FOH MIXING CONSOLE (Only digital):

- YAMAHA CL5, RIVAGE PM10
- Soundcraft Vi series
- MIDAS PRO series (no PRO1 please)
- DIGICO SD series (no sd11 please)
- AVID S6L or Venue Profile System

- Consoles YAMAHA LS9, Behringer X32, Presonus and similar – NO please

BACKLINE:

TAMA STARCLASSIC PERFORMER
Yamaha stage custom,
DW, PEARL
22' or 24 Bass Drum
13 (12)' Tom
16' Floor Tom

HARDWARE
Complete set of
Cymbals Stands (Min 4 + snare stand + hi-hat
stand)
Drum Chair
Carpet 3m x 2m

One (1) DRUM RISER 3m x 2m x 0.7m !!!
DRUM SHILD IS REQUIRED !!!

- **GUITAR (Dual combo stack is required)**

- Mesa/Boogie Dual Rectifier 100
- Engl Fireball 100
- Orange Dual Dark 100. cab A&B 4*12 + **footswitch!!!**
- One (1) active di-box for acoustic guitar
- One (1) bar chair for guitar player

- **BASS**

- One (1) Ampeg SVT classic ([Trace Elliot](#)) bass amplifier + 1 x 15' + 4 x 10' bass speaker cabinet (min. power 500w)
- One (1) active di-box

Three (3) heavy duty guitar stands

One (1) Music stand for leader speech

One (1) Fan for trumpet player

WIRELESS MICROPHONES:

We need four (4) wireless systems, transmitters/receivers. SHURE UR4+ (UR2 / BETA58A)

MONITORING:

- Twelve (12) Wedge 15" (d&b audiotechnik, Meyer Sound, L-Acoustics, Adamson, EAW)
- One (1) **Wireless monitors (in-ear) with earphones:**
 - Sennheiser SR2000 / SR3000 (preferred) or EW300 IEM G3 series
 - SHURE PSM 900 / 1000

All radio systems are obviously switched with active combiners with usage of outside antennas

We need 10 fresh AA batteries for wireless systems for each show

INPUT LIST /Patch List

Input	Instrument name	Signal	Stands, Sources	Note
1.	Kick out	Shure Beta 52A	Short boom	
2.	Kick in	Shure Beta 91A		+48v
3.	Snare top	Shure SM 57	Short boom	
4.	Snare bottom	Shure SM 57	Short boom	
5.	Hi Hat	Shure SM 81	Short boom	+48v
6.	Tom	Sennheiser E 904	Clip on	
7.	Floor Tom	Sennheiser E 904	Clip on	
8.	Overhead L	Shure SM 81	Tall boom	+48v
9.	Overhead R	Shure SM 81	Tall boom	+48v
10.	Ride	Shure SM 81	Short boom	+48v
11.	Bass	BSS AR133 or Klark DN100	Active DI	+48v
12.	Electric guitar L	Sennheiser E 906	Short boom	
13.	Electric guitar R	Sennheiser E 906	Short boom	
14.	Acoustic guitar	BSS AR133 or Klark DN100	Active DI	+48v
15.	Trombone	DPA 4099T	Clip on	+48v (XLR is needed)
16.	Trumpet	DPA 4099T (our)	Clip on (our)	+48v (XLR is needed)
17.	Rocket Tom	Shure SM 57	Short boom	
18.	Lead speech	Shure UR2/Beta 58A	Tall boom	Receivers located near the stage box
19.	Lead Voc	Shure UR2/Beta 58A	Tall boom	Receivers located near the stage box
20.	Vocal (Trombone)	Shure UR2/Beta 58A	Tall boom	Receivers located near the stage box
21.	Vocal (Trumpet)	Shure UR2/Beta 58A	Tall boom	Receivers located near the stage box
22.	Talk Back mic	Handheld mic with on/off switch		Located near the FOH

OUTPUT/Patch List

Output Buses	Name	Quantity	Note
1.	Mix 1 (Lead speech)	2 Wedges	
2.	Mix 2 (Lead Voc)	2 Wedges	
3.	Mix 3 (Trombone)	2 Wedges	
4.	Mix 4 (Trumpet)	2 Wedges	
5.	Mix 5 (Guitar)	2 Wedges	
6.	Mix 6 (Bass)	2 Wedges	
7.	Mix 7 (Drums)	XLR near drums	
8.	Mix 8 (Lead Voc)	1 Wireless In-ear	Transmitters located near the stage box

Stage Plan

